

KTM 390 ADVENTURE

COMPARISON BETWEEN VARIANTS



FEATURES	2023 390 ADV	390 ADV	390 ADV X
ENGINE TYPE	SINGLE CYLINDER, 4-VALVE, DOHC, F.I. ENGINE		
DISPLACEMENT	373.27 CC		
BORE / STROKE	89 MM X 60 MM		
POWER	43.5 PS (32 KW) @ 9,000 RPM		
TORQUE	37 NM @ 7,000 RPM		
FUEL INJECTION	BOSCH ELECTRONIC FUEL INJECTION (EFI)		
LUBRICATION	WET SUMP, FORCED		
COOLING	LIQUID COOLING WITH RADIATOR		
COMPRESSION RATIO	12.88:1		
FRONT SUSPENSION - MAKE - TYPE - TRAVEL - ADJUSTABILITY	WP APEX USD	WP APEX USD	WP APEX USD
	OPEN-CARTRIDGE FORKS	OPEN-CARTRIDGE FORKS	BIG-PISTON FORKS
	43 MM DIAMETER 170 MM TRAVEL	43 MM DIAMETER 170 MM TRAVEL	43 MM DIAMETER 170 MM TRAVEL
	COMPRESSION & REBOUND ADJUSTABLE (30 CLICKS EACH)		
REAR SUSPENSION - MAKE - TRAVEL - ADJUSTABILITY	WP APEX MONOSHOCK	WP APEX MONOSHOCK OPEN-CARTRIDGE FORKS	WP APEX MONOSHOCK BIG-PISTON FORKS
	177 MM WHEEL TRAVEL	177 MM WHEEL TRAVEL	177 MM WHEEL TRAVEL
	ADJUSTABLE FOR PRELOAD (10 STEPS) & REBOUND (20 CLICKS)	ADJUSTABLE FOR PRELOAD (10 STEPS)	ADJUSTABLE FOR PRELOAD (10 STEPS)
INSTRUMENT CLUSTER	TFT DISPLAY WITH HANDLEBAR MOUNTED CONTROLS		LCD DASH DISPLAY
RIDER AIDS	MTC, RIDING MODES, CORNERING ABS, OFFROAD ABS, RIDE-BY-WIRE, QUICKSHIFTER+, SLIPPER CLUTCH, 12V USB SOCKET		OFFROAD ABS, RIDE-BY-WIRE SLIPPER CLUTCH, 12V USB SOCKET
FRAME	SPLIT-TRELLIS FRAME (TUBULAR)		
WHEELS	SPOKED WHEELS WITH ALUMINUM RIMS 19"FR, 17"RR	5-SPOKE CAST ALLOY WHEELS. 19"FR, 17"RR	5-SPOKE CAST ALLOY WHEELS. 19"FR, 17"RR
FRONT BRAKE	320 MM DISC WITH RADIALLY MOUNTED CALIPER		
REAR BRAKE	230 MM DISC WITH FLOATING CALIPER		
FUEL TANK CAPACITY	14.5 L (400+ KMS TANK RANGE)		
GROUND CLEARANCE	200 MM		
SADDLE HEIGHT	855 MM		
KERB WEIGHT	177 KG		
STARTER / BATTERY	12 V, 8 AH MF BATTERY		
HEADLIGHT	FULL SPLIT LED HEADLAMP		
COLOUR OPTIONS	KTM RALLY ORANGE	ATLANTIC BLUE & DARK GALVANO BLACK	ELECTRONIC ORANGE & DARK GALVANO

*KTM 390 ADVENTURE is also available in low seat variant. Enquire at your nearest KTM STORE for availability.

#DARE2ADV